

## Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAS-25J2AVSG-ND1
Indoor unit	Hi-wall - HAORI	RAS-25N4KVRG-ND

### Function

Cooling	Y
Heating - Average	Y
Heating - Warmer	N
Heating - Colder	Y
Capacity control	Variable

### Design load

Cooling	Pdesignc	2.8	kW
Heating/Average	Pdesignh	2.7	kW
Heating/Colder	Pdesignh	4.0	kW

### Seasonal efficiency

Cooling	SEER	7.70	A++
Heating/Average	SCOP(A)	5.10	A+++
Heating/Colder	SCOP(C)	4.03	A+

## Cooling

Capacity				Efficiency			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	2.80	kW	Tj=35°C	EERd	4.31	
Tj=30°C	Pdc	2.06	kW	Tj=30°C	EERd	6.00	
Tj=25°C	Pdc	1.33	kW	Tj=25°C	EERd	10.95	
Tj=20°C	Pdc	1.30	kW	Tj=20°C	EERd	11.90	
					Degradation co-efficient cooling	Cdc	0,25

## Heating (Average climate)

Capacity				Efficiency			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	2.39	kW	Tj=-7°C	COPd	3.20	
Tj=2°C	Pdh	1.45	kW	Tj=2°C	COPd	5.25	
Tj=7°C	Pdh	0.93	kW	Tj=7°C	COPd	6.20	
Tj=12°C	Pdh	0.42	kW	Tj=12°C	COPd	7.50	
Tj=bivalent temperature	Pdh	2.70	kW	Tj=bivalent temperature	COPd	2.70	
Tj=operation limit	Pdh	2.60	kW	Tj=operation limit	COPd	2.00	
Bivalent temperature		-10	°C				
Operation limit temperature		-25	°C	Degradation co-efficient heating	Cdh	0,25	

## Heating (Colder climate)

### Capacity

Declared capacity for Heating/Colder climate at indoor temperature 20°C and outdoor temperature Tj.

### Efficiency

Declared coefficient of performance for Heating/Colder climate at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	2.39 kW	Tj=-7°C	COPd	3.20
Tj=2°C	Pdh	1.45 kW	Tj=2°C	COPd	5.25
Tj=7°C	Pdh	0.93 kW	Tj=7°C	COPd	6.20
Tj=12°C	Pdh	0.42 kW	Tj=12°C	COPd	7.50
Tj=bivalent temperature	Pdh	2.74 kW	Tj=bivalent temperature	COPd	2.40
Tj=operation limit	Pdh	2.60 kW	Tj=operation limit	COPd	2.00
Tj=-15°C	Pdh	3.26 kW	Tj=-15°C	COPd	2.40
Bivalent temperature		Tbiv	X °C		
Operation limit temperature		Tol	X °C		

## Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

Off mode	Poff	0.001 kW	Cooling	QCE	127 kWh/a
Standby mode	Psb	0.001 kW	Heating/Average	QHE/A	741 kWh/a
Thermostat-off mode	Pto	0.037 kW	Heating/Warmer	QHE/B	x kWh/a
Crankcase heater mode	Pck	0.000 kW	Heating/Colder	QHE/C	2087 kWh/a

## Refrigerant

Type		R-32			
Weight			0.76 kg		
Global Warming Potential	GWP		675 kgCO <sub>2</sub> eq.		

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAS-25J2AVSG-ND1	59	61	RAS-25J2AVSG-ND1		
RAS-25N4KVRG-ND	55	58	RAS-25N4KVRG-ND		

## Dimensions

	Height	Width	Depth	Weight
RAS-25J2AVSG-ND1	mm	mm	mm	kg
RAS-25N4KVRG-ND	mm	mm	mm	kg

Harmonised standard	EN14511:2007, EN12102
Calculation methods - Measurement standards	PrEN 14825: 2011 chapter 8 and 9

Contact details for obtaining more information

Importer/Distributor in EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom

---